

Abstracta AB
Box 75
363 03 LAMMHULT
SWEDEN

Testing of work tables and desks according to EN 527-1, -2 (4 appendices)

Customer:	Abstracta AB
Test object/ID:	Work table/dB-acoustic booth
Test method:	EN 527-1:2011 Office furniture - Work tables and desks – Dimensions EN 527-2:2016 Office furniture - Work tables - Safety, strength and durability requirements
Scope:	Complete test
Date of test:	2020-01-23 – 2020-03-06
Test result:	The tested object passed the test Dimensionally according EN 527-1: Type D Sit/stand Information for use has not been assessed
Reservation:	The test results in this report apply solely to the specimen tested
Test environment:	23 ± 2°C and 50 ± 5% relative humidity

RISE Research Institutes of Sweden AB Building Technology - Wood Technological Assessment

Performed by

Examined by

Robert Almqvist

Bengt-Åke Andersson

Appendices

1. Dimensions (1 page)
2. Strength and durability(2 pages)
3. Description of test object (1 page)
3. Pictures (3 pages)

RISE Research Institutes of Sweden AB

Postal address	Office location	Phone / Fax / E-mail
Box 857	Brinellgatan 4	+46 10 516 50 00
SE-501 15 BORÅS	SE-504 62 BORÅS	+46 33 13 55 02
Sweden		info@ri.se

This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Appendix 1

Dimensions according to EN 527-1:2011

Abbreviations: N/A = Not applicable
N/T = Not tested

Table 1

1.	EN 527-1	Dimensions for Type D-table Sit/stand	Requirements (mm)	Measured dimensions (mm)	Results
1.1	h_1	Height of the work surface Sit/stand	680 - 1180	660 - 1200	Pass
1.2	t_1	Maximum desk top thickness (front)	≤ 70	22	Pass
1.3	t_2	Maximum desk top thickness (500 mm from the edge)	≤ 100	89	Pass
1.4	k_1	Minimum height of knee clearance for standing position only (applies only to tables with a height more than 850 mm)	≥ 700	>700	Pass
1.5	k_2	Minimum depth of knee clearance for standing position only	≥ 80	>80	Pass
1.6	k_3	Minimum depth of foot clearance for standing position only	≥ 150	>150	Pass
1.7	f_1	Minimum height of minimum foot clearance: From 600 to 800 mm from the front edge	≥ 120	>120	Pass
1.8	f_2	Minimum height of minimum foot clearance: From front edge to 150 mm (standing only)	≥ 120	>120	Pass
1.9	g_1	Minimum legroom depth	≥ 800	800	Pass
1.10	D	Minimum desk top depth	≥ 800	800	Pass
1.11	W	Minimum legroom width - Sitting only and sit/stand	≥ 850	1490	Pass

Appendix 2

Strength and durability according to EN 527-2:2016

Abbreviations: N/A = Not applicable
N/T = Not tested

Note. In some case, the standard allows different loading than the nominal to prevent the test object from overturning, these loads are reported in **bold italic**

Table 2

2.	Strength, durability	EN 1730:2012	Cycles	Loading nominal	Results
2.1	Durability of electrically operated height adjustment mechanisms	8.2	5000	50 kg ^c	Pass
2.2	Horizontal static load test ^a - Longitudinal direction - Transverse direction	6.2	10 10	450 N 450 N	Pass Pass
2.3	Additional horizontal static load test for adjustable tables with a height more than 950 mm ^b - Longitudinal direction - Transverse direction	6.2	10 10	237 N 237 N	Pass Pass
2.4	Vertical static load tests ^a	6.3.1	10	1000 N	Pass
2.5	Additional vertical static load test for adjustable tables with a height more than 950 mm ^b	6.3.1	10	500 N	Pass
2.6	Horizontal durability test ^a - Longitudinal direction - Transverse direction	6.4.2	10000	300 N 300 N	Pass Pass
2.7	Stiffness of the structure ^a - Longitudinal direction, max 17mm/m - Transverse direction, max 17 mm/m	6.4.3	1	200 N 200 N	Pass 14 mm/m 4 mm/m
2.8	Vertical durability test ^a	6.5	10000	400 N	Pass
2.9	Durability of tables with castors	6.8	2000	Load on table top 50 kg	N/A
2.10	Vertical impact test ^a	6.6	10	Drop height 140 mm	Pass
2.11	Drop test ^a Drop height calculated according to table 1 in EN 1730:2012	6.9	6/3	Drop height 30 mm	Pass
2.12	Stability under vertical load	7.2		750 N	Pass
2.13	Stability for work tables with extension elements	7.3		400 N	N/A
<p>a Height adjustable tables shall be adjusted to maximum 950 mm b Height adjustable tables shall be adjusted to maximum height c Nominal load according to the manufacturer's instruction but not less than 50 kg</p>					

Appendix 2

Table 3

3.	General safety requirements / Shear and squeeze points	EN 527-2	Results
3.1	<p>The table shall be designed so as to minimize the risk of injury to the user</p> <p>All parts of the table with which the user comes into contact during intended use, shall be designed so that physical injury and damage are avoided</p> <p>These requirements are fulfilled when:</p> <ul style="list-style-type: none"> a) All accessible edges and corners are free from burrs and rounded or chamfered b) Edges and corners of the top surfaces are chamfered not less than 1 mm by 1 mm or rounded with a radius of not less than 2 mm c) Ends of feet and tubular components are closed or capped <p>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided</p> <p>It shall not be possible for any load bearing part of the table to come loose unintentionally</p> <p>All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use</p> <p>The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 4.1</p> <p>There shall be no shear and squeeze points which close to less than 25 mm unless they are always less than 7 mm created by parts of the table operated by powered mechanisms, i.e. springs, gas lifts and motorized systems</p> <p>There shall be no shear and squeeze points which close to less than 25 mm unless they are always less than 7 mm created by forces applied during normal use or created by the user during normal movements and actions, e.g. attempting to move the table</p>	4.1- 4.2	Pass

Table 4

4.	Information for use	EN 527-2	Results
4.1	<ul style="list-style-type: none"> a) Information regarding intended use b) Instruction for operating the adjusting mechanisms c) Instruction for the care and maintenance of the table 	6.	Not Assessed

Appendix 3

Description of test object

Test object/ID: Work table/dB-acoustic booth

Dimensions

Width: 168 cm
Depth: 86 cm
Height: 66 – 120 cm
Mass: 83 kg

Components

Frame/legs: L-shaped aluminium 4 mm/28 mm metal tube
Table top: Laminated MDF 22 mm
Functions: Adjustable in height
Actuator: OKIN

Sampling: The test object was selected by the customer
Date of arrival at
RISE test laboratory: 2019-12-12
Observed defects before testing: No defects

Appendix 4

Pictures

Figure 1



Figure 2

Appendix 4




Figure 3



Figure 4

Appendix 4



Figure 5



Figure 6